

APP CRS  
031°

Rwy Idg  
TDZE  
Apt Elev

4000  
648  
658

RNAV (GPS) RWY 3

RUBY (RBY) (PARY)

When local altimeter setting not received, use Galena altimeter setting and increase all MDA 340 feet and all visibilities ¾ SM. DME/DME RNP-0.3 NA.  
Rwy 3 Straight-in and Circling minimums NA at night. Helicopter visibility reduction below 1 SM NA.

MISSED APPROACH:  
Climbing right turn to 3800 direct WINUR and hold.

|                   |                                 |                           |               |
|-------------------|---------------------------------|---------------------------|---------------|
| AWOS-3P<br>118.25 | ANCHORAGE CENTER<br>127.0 290.2 | FAIRBANKS RADIO<br>122.25 | CTAF<br>122.8 |
|-------------------|---------------------------------|---------------------------|---------------|

The main chart displays the RNAV route for RWY 3. Key waypoints and data include:  
- WINUR: 3800 ft, 30 NM to WINUR (NoPT), 5 NM holding pattern.  
- ZUMUN: 3800 ft, 30 NM to ZUMUN, 10 NM to ZUMUN.  
- YARUN: 2700 ft, 2.9 NM to SOLCO.  
- SOLCO: 4600 ft, 30 NM to DUCCEL.  
- DUCCEL: 3800 ft, 30 NM to DUCCEL.  
- Altitudes: 2988±, 1961, 1410, 1780, 658, 648.  
- Angles: 120°, 211°, 030°, 031°, 210°, 301°.

5 NM Holding Pattern

WINUR

Visual Segment - Obstacles.

3800

WINUR

2700

1800

6.2 NM

3.2 NM

2.9 NM

0.1

| CATEGORY | A                     | B                     | C                       | D  |
|----------|-----------------------|-----------------------|-------------------------|----|
| LNVA MDA | 1260-1                | 612 (700-1)           | 1260-1¾<br>612 (700-1¾) | NA |
| CIRCLING | 1260-1<br>602 (700-1) | 1400-1<br>742 (800-1) | 1400-2¼<br>742 (800-2¼) | NA |

REIL Rwy 21

MIRL Rwy 3-21

RUBY, ALASKA

Amtd 1C 02DEC21

64°44'N-155°28'W

RUBY (RBY) (PARY)

RNAV (GPS) RWY 3