ILS Y or LOC Y RWY 10R

CHICAGO O'HARE INTL (ORD)

LOC/DME I-BYW	APP CRS	Rwy Idg	7500
110.9	091°	TDZE	680
Chan 46		Apt Elev	680

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.
Simultaneous approach authorized.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	133.0 348.0	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	

ALTERNATE MISSED APCH FIX
JOLIET
JOT
112.3
Chan 70
R-246 066° 246°

MSA ORD 25 NM
3400

113.0 OBK Chan 77
113.0 OBK Chan 77
R-195
R-185

(IAF) GIBNS
FERLL I-BYW 27.8 RADAR
MLSEN I-BYW 24.7 RADAR
OLLGA I-BYW 21.5 RADAR
LEATH I-BYW 18.4 RADAR
(IF) GOOZY I-BYW 15.3 RADAR
KVENN I-BYW 12.1 RADAR
FLLYN INT I-BYW 6.6 RADAR
TRUFL INT I-BYW 3.5
WUGIX I-BYW 2.1

271°
8000 091° (3.1)
7000 (3.1)
6000 (3.1)
5000 (3.1)
4000 (3.1)
2300 091° (5.6)
9000 087° (20.1)
1468
883
852
1508
1185
813
807

R-248 068° 248°
DUPAGE
108.4 DPA
Chan 21

LOCALIZER 110.9
I-BYW
Chan 46
LOC offset 2.50°

1200 4000 DPA
* LOC only.

9000 091° 8000 7000 6000 5000 4000 2300 *1220
*I-BYW 2.9
GS 3.00°
TCH 55

3.1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 5.6 NM 3.1 NM 0.6 0.8 0.4

CATEGORY	A	B	C	D
S-ILS 10R	930/24 250 (300-½)			
S-LOC 10R	1220/24 540 (600-½)		1220/55 540 (600-1)	
TRUFL FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 10R	1120/24 440 (500-½)		1120/40 440 (500-¾)	

ELEV 680 D TDZE 680

7500 X 150
TWR 914
11245 X 200
11260 X 150
0.3% DOWN
TWR 910
13000 X 150
10800 X 200
TWR 876
0.3% UP
7500 X 150
091°

HIRL all Rwys
TDZ/CL all Rwys except 4L

FAF to MAP 4.5 NM

Knots	60	90	120	150	180
Min:Sec	4:30	3:00	2:15	1:48	1:30

EC-3, 11 JUL 2024 to 08 AUG 2024
EC-3, 11 JUL 2024 to 08 AUG 2024