


WAAS CH 49216 W 27A	APP CRS 270°	Rwy Idg 10000 TDZE 6765 Apr Elev 6765
---	------------------------	--


RNAV (GPS) RWY 27

SOUTHWEST WYOMING RGNL (R.K.S)


RNP APCH.		MALSR	MISSED APPROACH: Climb to 9800 direct REGVE and hold.
<p>▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -27°C or above 44°C. For inop ALS increase LNAV/VNAV all Cats visibility to ½ SM.</p>			
ASOS 118.375	SALT LAKE CENTER 124.35 353.5	UNICOM 122.8 (CTAF) 0	



Procedure NA for arrivals at OCS VOR/DME on V235 southwest bound, V187 north and southbound and T298 southwest bound.



ELEV 6765	D	TDZE 6765
-----------	----------	-----------



9800	REGVE				
*LNAV only.		WATUM 3.1 NM to RW27	HEBUM 8700	EPULE 9300	DIGNE 7 NM Holding Pattern
0.9 NM to RW27		7800	8700	9300	14000 9300
GP 3.00° TCH 55					
CATEGORY	A	B	C	D	
LPV DA	6965-½		200 (200-½)		
LNAV/VNAV DA	7036-½		271 (300-½)		
LNAV MDA	7100-½		335 (400-½)		
C CIRCLING	7140-1 375 (400-1)	7220-1 455 (500-1)	7220-1½ 455 (500-1½)	7540-2 ½ 775 (800-2 ½)	

NW-1, 11 JUL 2024 to 08 AUG 2024

NW-1, 11 JUL 2024 to 08 AUG 2024