

ANCHORAGE DEP CON
126.4 270.25
D-ATIS
135.5
CLNC DEL
119.4 323.1
GND CON
121.9 338.25
ANCHORAGE TOWER
118.3 257.8

RADAR required.

TOP ALTITUDE:
4000

BIG LAKE
112.5 BGQ
Chan 72

ANCHORAGE
113.15 TED
Chan 78(Y)


SPARREVOHN
117.2 SQA
Chan 119

KENAI
117.6 ENA
Chan 123

JOHNSTONE POINT
116.7 JOH
Chan 114

HOMER
114.6 HOM
Chan 93

MIDDLETON ISLAND
115.3 MDO
Chan 100



TAKEOFF MINIMUMS

Rwys 15, 25L/R, 33: NA - ATC.

Rwy 7L: 300-1½ or standard with minimum climb of 255 feet per NM to 400.

Rwy 7R: 300-1 or standard with minimum climb of 285 feet per NM to 400.

NOTE: Do not exceed 200K.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 7L/R: Climb on heading 074° to 600, then climbing right turn on heading 199°. Thence. . .

. . . expect RADAR vectors to assigned route or depicted fix. Maintain 4000. Expect further clearance to filed altitude within 10 minutes after departure.