

WAAS

CH **99303**

W20A

APP CRS

201°

Rwy Idg

8000

TDZE

871

Apt Elev

871

RNAV (GPS) RWY 20

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using General Downing-Peoria Intl altimeter setting. When local altimeter setting not received, use General Downing-Peoria Intl altimeter setting: increase all DA 116 feet and all MDA 120 feet; increase LPV all Cats visibility to ¾ mile, LNAV/VNAV all Cats visibility to 1 ¾ mile, LNAV Cats C/D visibility to 1 mile, and Circling Cats C/D visibility ¾ mile. For inop ALSF increase LNAV Cat C/D visibility to RVR 6000. For inoperative ALSF-2 when using General Downing-Peoria Intl altimeter setting increase LPV all Cats visibility to RVR 6000.

ALSF-2

Ⓐ

⏏

⏏

⏏

MISSED APPROACH:

Climb to 3000 direct JINUB and on track 288° to MCLEN and hold.

ATIS 119.575	SAINT LOUIS APP CON 128.725 256.9	BLOOMINGTON TOWER ★ 124.6 (CTAF) 0 269.575	GND CON 121.65	UNICOM 122.95
------------------------	---	---	--------------------------	-------------------------

Procedure NA for arrivals at PNT VOR/DME via V313 northbound.

Procedure NA for arrivals at JILLY via V173 northeast bound.

MSA RW20 25 NM
2800

3000

JINUB

tr 288°

MCLEN

UDIYO

2500

RUNAE

4 NM Holding Pattern

*LNAV only

*1.1 NM to RW20

RW20

GP 3.00° TCH 55

1.1

3.8 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	1121/24	250 (300-½)		
LNAV/VNAV DA	1301/50	430 (500-1)		
LNAV MDA	1280/24	409 (500-½)	1280/40	409 (500-¾)
CIRCLING	1340-1	469 (500-1)	1620-2¼ 749 (800-2¼)	1620-2½ 749 (800-2½)

TDZ/CL Rwy 20 **0**

HIRL Rwy 2-20 and 11-29 **0**

BLOOMINGTON/NORMAL, ILLINOIS

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

Amdt 1A 15OCT15

40°29'N-88°55'W

RNAV (GPS) RWY 20