



WAAS CH 56436 W20A	APP CRS 199°	Rwy Idg TDZE Apt Elev	6506 303 303
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20
HEART OF GEORGIA RGNL (E2M)

⚠ Baro-VNAV NA when using Dublin altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). When local altimeter setting not received, use Dublin altimeter setting and increase all DA 52 feet and all MDA 60 feet; increase LPV all Cats and LNAV Cat C/D visibility ¼ mile and LNAV/VNAV all Cats and Circling Cat C visibility ¼ mile. DME/DME RNP-0.3 NA. VDP NA with Dublin altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2000 direct CENVA and hold.

ATIS 119.425	JACKSONVILLE CENTER 127.575 269.025	HEART OF GEORGIA TOWER ★ 124.55 (CTAF) 0	GND CON 121.175	UNICOM 122.95
------------------------	---	--	---------------------------	-------------------------



2000	CENVA	ESMUY 2.9 NM to RW20	LAPTE 2000	UCALA 2100	GP 3.00° TCH 45
*LNAV only.	*1.2 NM to RW20	*1.7 NM	2.3 NM	8.6 NM	
1.2	1.7 NM	2.3 NM	8.6 NM		
CATEGORY	A	B	C	D	
LPV DA	602-1	299 (300-1)			
LNAV/VNAV DA	722-1⅓	417 (500-1⅓)			
LNAV MDA	720-1	417 (500-1)	720-1¼	417 (500-1¼)	
CIRCLING	760-1 457 (500-1)	820-1 517 (600-1)	900-1½ 597 (600-1½)	900-2 597 (600-2)	