RNAV (GPS) RWY 36L

DALLAS-FORT WORTH INTL (DFW)

WAAS	APP CRS	Rwy Idg	13400
CH 93805	356°	TDZE	588
W36B		Apt Elev	607

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). For inop MALSR, increase LNAV Cat C/D visibility to RVR 5500. Simultaneous approach authorized with Rwy 35L/C/R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3000 direct KAGLE and hold.

D-ATIS	REGIONAL APP CON	DFW TOWER	GND CON	CLNC DEL	CPDLC
ARR 123.775	118.425	126.55 127.5 EAST	121.65 121.8 EAST	128.25	
DEP 135.925		124.15 134.9 WEST	121.85 WEST		

MISSED APCH FIX

128° KAGLE 4 NM 308°

804 1016

641 RW36L 660±

CIRIS 1.4 NM to RW36L 704

(FAF) BOBIN

2300 (2.5)

CHAAR

3000 356° (6.3)

HUTEN

3000 356° (3.2)

(IF) ALLIN 2549

MSA RW36L 25 NM

3600

RADAR REQUIRED

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

1100 3000 KAGLE

*LNAV only.



CATEGORY	A	B	C	D
LPV DA	788/18 200 (200-½)			
LNAV/VNAV DA	987/45 399 (400-⅞)			
LNAV MDA	960/24 372 (400-½)		960/35 372 (400-⅝)	

ELEV 607 D TDZE 588



HIRL all Rwys
REIL Rwys 13L and 31L
TDZ/CL all Rwys except 13L and 31L

SC-2, 11 JUL 2024 to 08 AUG 2024
SC-2, 11 JUL 2024 to 08 AUG 2024