RNAV (GPS) Y RWY 16R

DENVER INTL (DEN)

WAAS	APP CRS	Rwy Idg	16000
CH 53546	170°	TDZE	5326
W16B		Apt Elev	5434

RNP APCH - GPS.

T LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -24°C or above 54°C. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000. Simultaneous approach authorized.

MALSR (A5)

MISSED APPROACH: Climb to 5900, then climbing right turn to 10000 direct BINBE and hold, continue climb-in-hold to 10000.

D-ATIS	DENVER APP CON		DENVER TOWER	GND CON	CLNC DEL	CPDLC
ARR 125.6 379.9	119.3 307.3	120.35 379.3	135.3 351.95	121.35 379.175	118.75	
DEP 134.025	(NORTH)	(SOUTH)				



MISSED APCH FIX





CATEGORY	A	B	C	D
LPV DA	5576/24 250 (200-½)			
LNAV/VNAV DA	5582/24 256 (200-½)			
LNAV MDA	5660/24 334 (300-½)		5660/26 334 (300-½)	

HIRL all Rwys
TDZ/CL Rwys 7, 16L, 16R, 17R, 26, 34L, 34R, 35L, 35R

SW-1, 11 JUL 2024 to 08 AUG 2024
SW-1, 11 JUL 2024 to 08 AUG 2024