

RNAV-1 DME/DME/IRU or GPS.
RADAR required.

**TOP ALTITUDE:
ASSIGNED BY ATC**

NOTE: Jet aircraft only.
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.
NOTE: SHAQQ and BAGGS transitions ATC assigned except aircraft departing MIA.

MIAMI DEP CON
119.45 290.325
ATIS
125.9
CLINC DEL
119.2
GND CON
120.025
OPA LOCKA TOWER ★
134.675 (CTAF)

GLADZ THREE DEPARTURE (RNAV)
(GLADZ3.GLADZ) 21 MAR 24

(GLADZ3.GLADZ) 24081
GLADZ THREE DEPARTURE (RNAV)

AL-256 (FAA)

MIAMI-OPA LOCKA EXEC (OPF)
MIAMI, FLORIDA

SHAQQ

FL180
*1300
278°
(93)

FL180
*1400
328°
(94)

MARCI

17000
*1400
302°
(33)



GLADZ

258°
(20)

RUTLG

258°
(9)

GAYTR
5000



WIGNA

FL180
*1300
227°
(39)

FL180
*1300
203°
(43)

LULLS

TAKEOFF MINIMUMS
Rwys 27L, 30: Standard.
Rwy 9L: Standard with minimum climb of 500'/NM to 1000.
Rwy 9R: Standard with minimum climb of 500'/NM to 700.
Rwys 12, 27R: Standard with minimum climb of 500'/NM to 600.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

MIAMI, FLORIDA
MIAMI-OPA LOCKA EXEC (OPF)

GLADZ THREE DEPARTURE (RNAV)



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 9L/R: Climb on heading 093° or as assigned by ATC for RADAR vectors to cross GAYTR at or above 5000, thence. . . .

TAKEOFF RUNWAY 12: Climb on heading 128° or as assigned by ATC for RADAR vectors to cross GAYTR at or above 5000, thence. . . .

TAKEOFF RUNWAYS 27L/R: Climb on heading 273° or as assigned by ATC for RADAR vectors to cross GAYTR at or above 5000, thence. . . .

TAKEOFF RUNWAY 30: Climb on heading 308° or as assigned by ATC for RADAR vectors to cross GAYTR at or above 5000, thence. . . .

. . . on track 258° to RUTLG, then on track 258° to GLADZ, then on transition. Maintain ATC assigned altitude, expect clearance to filed altitude 10 minutes after departure.

BAGGS TRANSITION (GLADZ3.BAGGS)

LULLS TRANSITION (GLADZ3.LULLS)

SHAQQ TRANSITION (GLADZ3.SHAQQ)

SE-3, 05 SEP 2024 to 03 OCT 2024

SE-3, 05 SEP 2024 to 03 OCT 2024