

WAAS CH 70310 W13A	APP CRS 131°	Rwy ldg 6568 TDZE 46 Apt Elev 46
--	------------------------	---

RNAV (GPS) RWY 13R
WILLIAM P HOBBY (HOU)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. DME/DME RNP-0.3 NA. For inop ALS, increase LPV all Cats visibility to RVR 5000; increase LNAV/VNAV Cats A/B/C/D visibility to 1½ SM, Cat E to 1½ SM; and increase LNAV Cats A/B visibility to RVR 5500, Cats C/D to 1½ SM, Cat E to 1¾ SM. Rwy 13R helicopter visibility reduction below ¾ SM NA.

MALSR



MISSED APPROACH: Climb to 2200 direct LESLO and on track 134° to VUH VOR/DME.

D-ATIS 124.6	HOUSTON APP CON 120.05 379.1 EAST 124.35 316.15 WEST	HOBBY TOWER 118.7 256.9	GND CON 121.9	CLNC DEL 125.45	CPDLC
------------------------	--	-----------------------------------	-------------------------	---------------------------	-------



JABBS		ROYCE		2200 ↑	LESLO ✦	tr 134°	VUH ◻
2000		2000		*1.4 NM to RW13R			
GP 3.00° TCH 49		2000		*LNAV only			
7.7 NM		4.5 NM		1.4 NM			
CATEGORY	A	B	C	D	E		
LPV DA	330/40			284 (300-¾)			
LNAV/ VNAV	475/50			429 (500-1)			
LNAV MDA	540/40	494 (500-¾)		540/50	494 (500-1)		540/60 494 (500-1¼)
CIRCLING	540-1	494 (500-1)		740-2¼	694 (700-2¼)		860-3 814 (900-3)

