


WAAS CH <b>61300</b> <b>W29A</b>	APP CRS <b>295°</b>	Rwy Idg TDZE Apt Elev	<b>5500</b> <b>619</b> <b>632</b>
----------------------------------------	------------------------	-----------------------------	-----------------------------------------



# RNAV (GPS) RWY 29

BUTLER COUNTY RGNL/HOGAN FLD (HAO)

RNP APCH - GPS.			MALS	MISSED APPROACH: Climb to 2700 direct MONTR and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. Inop table does not apply to LPV.				
ASOS <b>121.425</b>	CINCINNATI APP CON <b>121.0 254.25</b>	CLNC DEL <b>126.25</b>	UNICOM <b>123.05 (CTAF) 1</b>	



ELEV <b>632</b>	TDZE <b>619</b>
-----------------	-----------------



	1.3	2 NM	2.8 NM	8.1 NM	
CATEGORY	A	B	C	D	
LPV DA		819-3/4	200 (200-3/4)		
LNAV/VNAV DA		1080-1 1/8	461 (500-1 1/8)		
LNAV MDA	1080-3/4	461 (500-3/4)	1080-1 1/8	461 (500-1 1/8)	
CIRCLING	1280-1	648 (700-1)	1300-1 3/4 668 (700-1 3/4)	1760-3 1128 (1200-3)	