WAAS CH 65614 W04A	APP CRS 047°	Rwy Idg 5927 TDZE 619 Apt Elev 620

RNAV (GPS) Z RWY 4R

CHICAGO MIDWAY INTL (MDW)

RNP APCH - GPS

Circling Rwy 31R NA at night.
Rwy 4R helicopter visibility reduction below RVR 4000 NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C.

MISSED APPROACH: Climb to 1100 then climbing right turn to 2600 direct EON VORTAC and hold.

D-ATIS	CHICAGO APP CON	MIDWAY TOWER	GND CON	CLNC DEL	CPDLC
132.75	128.2 353.875	135.2 269.125	118.075	124.625	



ELEV 620	D	TDZE 619

HIRL Rwys 4R-22L and 13C-31C
MIRL Rwys 4L-22R, 13L-31R, and 13R-31L
REIL Rwys 4R, 22L, and 31C
RLLS Rwys 13C and 31C



CATEGORY	A	B	C	D
LPV DA	869/40	250 (300-¾)		
LNAV/VNAV DA	1097-1⅜	478 (500-1⅜)		
LNAV MDA	1080/55	461 (500-1)	1080-1⅜	461 (500-1⅜)
C CIRCLING	1120-1	500 (500-1)	1340-2	1340-2¼
			720 (800-2)	720 (800-2¼)



EC-3, 31 OCT 2024 to 28 NOV 2024
EC-3, 31 OCT 2024 to 28 NOV 2024