WAAS	APP CRS	Rwy Idg	9000
CH 82707	295°	TDZE	5599
W30B		Apt Elev	5673

RNAV (GPS) RWY 30R

ROCKY MOUNTAIN METRO (BJC)

T NA Baro-VNAV and VDP NA when using Denver Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C (-14°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Denver Intl altimeter setting and increase all DA 82 feet and all MDA 100 feet, increase LNAV/VNAV all Cats, LNAV Cat C/D and Circling Cat C visibility ¼ mile. For inoperative MALSR, increase LNAV/VNAV all Cats visibility to 1⅛ mile and LNAV Cat C/D visibility to 1 mile. For inoperative MALSR, when using Denver Intl altimeter setting, increase LPV all Cats visibility to 1 mile, LNAV/VNAV all Cats visibility to 1⅜ mile and LNAV Cat A/B visibility to 1 mile and Cat C/D visibility to 1⅜ mile.

MALSR (A5)

MISSED APPROACH: Climb to 6300 then climbing right turn to 10300 direct HYGEN and hold, continue climb-in-hold to 10300.

ATIS	DENVER APP CON	METRO TOWER★	GND CON	CLNC DEL
126.25	125.12 263.02	118.6 (CTAF) L 233.7	121.7	132.6

RADAR REQUIRED

MISSED APCH FIX
HYGEN
128° 308° 7 NM

(IAF) ROKXX 210K
7000 128° (7.3)
PLAAY
7000 190° (3.5)
LAWNG 7000
7000 245° (2.9)
(IF) BAAWL 7000
7000 351° (3.6)
(IAF) NSPYR

(FAF) ALIKE
7000 295° (4)
5824
VOGFA 1.9 NM to RW30R
RW30R
5928 5616 6529 6204 8945 7000 7080 8680

MSA RW30R 25 NM
14800

ELEV 5673 D TDZE 5599

TWR 5680
12L-12R 12.0% DOWN 9000 X 100
7002 X 75
3-21 9000 X 150 10.9%
1.1% UP 1.1% UP
30L 30R
295° to RW30R

HIRL Rwys 12L-30R L
MIRL Rwys 3-21 and 12R-30L L
REIL Rwys 12L, 12R and 30L L

6300 10300 HYGEN
*LNAV only.
*1 NM to RW30R
VOGFA 1.9 NM to RW30R
ALIKE 7000
BAAWL
295° 7000
7000
RW30R
6220*
GP 3.00°
TCH 52
1 NM 0.9 2.4 NM 4 NM

CATEGORY	A	B	C	D
LPV DA	5799-½ 200 (200-½)			
LNAV/VNAV DA	5900-⅝ 301 (300-⅝)			
LNAV MDA	5940-½ 341 (300-½)		5940-⅝ 341 (300-⅝)	
C CIRCLING	6180-1 507 (600-1)	6240-1 567 (600-1)	6360-2 687 (700-2)	6860-3 1187 (1200-3)

SW-1, 31 OCT 2024 to 28 NOV 2024
SW-1, 31 OCT 2024 to 28 NOV 2024