


LOC I-AUG 108.7	APP CRS 171°	Rwy Idg 5002	TDZE 348
		Apt Elev 352	

ILS or LOC RWY 17



AUGUSTA STATE (AUG)

ADF required.

Localizer unusable from 0.5 NM to threshold above 1500 feet. When local altimeter setting not received, use Waterville altimeter setting; increase S-ILS 17 DA to 583; increase all MDAs 40 feet and visibility S-LOC 17 Cat C and D 1/8 SM, and Circling Cat D 1/4 SM; SHAWE fix minimums increase S-LOC 17 Cat C and D visibility 1/8 SM, and Circling Cat D visibility 1/4 SM. Glideslope unusable below 430 feet. Circling Rwy 8, 26 NA at night. # DME from AUG VOR/DME.

MALS  MISSED APPROACH: Climb to 1000 then climbing left turn to 2500 direct DUNNS LOM and hold.

ASOS 118.325	PORTLAND APP CON ★ 128.35 299.2	CLNC DEL 119.95 299.2	UNICOM 123.0 (CTAF)
------------------------	---	---------------------------------	-------------------------------



ELEV 352	D	TDZE 348
----------	---	----------

HIRL Rwy 17-35	8
MIRL Rwy 8-26	8
REIL Rwy 35	8

FAF to MAP 5.6 NM					
Knots	60	90	120	150	180
Min:Sec	5:36	3:44	2:48	2:14	1:52

CATEGORY	A	B	C	D
S-ILS 17	548-1/2		200 (200-1/2)	
S-LOC 17	900-1/2	552 (600-1/2)	900-1 1/4	552 (600-1 1/4)
CIRCLING	940-1	980-1	980-1 3/4	1160-2 1/2
	588 (600-1)	628 (700-1)	628 (700-1 3/4)	808 (900-2 1/2)
SHAWE FIX MINIMUMS #				
S-LOC 17	620-1/2 272 (300-1/2)			
CIRCLING	940-1	980-1	980-1 3/4	1160-2 1/2
	588 (600-1)	628 (700-1)	628 (700-1 3/4)	808 (900-2 1/2)