APP CRS	Rwy Idg	10000
050°	TDZE	791
	Apt Elev	796

RNAV (RNP) Z RWY 5R
INDIANAPOLIS INTL (IND)

For uncompensated Baro-VNAV systems, procedure NA below -18°C (0°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized, for arrivals from IIUUU only.

ALSF-2

MISSED APPROACH: Climb to 1500, then climbing right turn to 3000 direct OZMOE and hold.

D-ATIS	INDIANAPOLIS APP CON	INDY TOWER	GND CON	CLNC DEL	CPDLC
134.25	128.175 317.8	120.9 257.8	121.9	128.75 257.8	



MISSED APCH FIX

ELEV 796 D TDZE 791

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

1500	3000	OZMOE
↑	↗	△

See planview for multiple IF locations.





CATEGORY	A	B	C	D
RNP 0.11 DA	1174/45 383 (400-⅞)			
RNP 0.30 DA	1271/60 480 (500-1¼)			

AUTHORIZATION REQUIRED

HIRL all Rwys
TDZ/CL Rwys 5L and 5R

EC-2, 28 NOV 2024 to 26 DEC 2024
EC-2, 28 NOV 2024 to 26 DEC 2024