

EVAN THREE DEPARTURE (RNAV)

TOP ALTITUDE:
4000

TAKEOFF MINIMUMS:

Rwys 2C, 2L, 2R, 13, 20C, 20L, 20R, 31: Standard
with minimum climb of 500' per NM to 1100.

NOTE: DME/DME/IRU or GPS required.


NOTE: RNAV 1.

NOTE: Radar required.

NOTE: For Turbojet aircraft only.

NOTE: Transponder code will be issued via PDC or
Nashville clearance delivery.


NOTE: If unable to accept climb rates, advise ATC
on initial contact.



NOTE: Chart not to scale.

SE-1, 28 NOV 2024 to 26 DEC 2024

- D-ATIS 135.1
- CLNC DEL 126.05
- CPDLC
- GND CON
- 121.9 348.6
- NASHVILLE TOWER
- 118.6 257.8
- NASHVILLE DEP CON
- 118.4 360.7



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 2L/C/R: Climb heading 021° or assigned ATC heading, thence....
TAKEOFF RWY 13: Climb heading 136° or assigned ATC heading, thence....
TAKEOFF RWYS 20L/C/R: Climb heading 201° or assigned ATC heading, thence....
TAKEOFF RWY 31: Climb heading 316° or assigned ATC heading, thence....
expect radar vectors to CHPPY, then on track 115° to EVVAN. Maintain 4000,
 expect clearance to filed altitude within five (5) minutes after departure.

SE-1, 28 NOV 2024 to 26 DEC 2024

EVAN THREE DEPARTURE (RNAV)