ILS or LOC RWY 4

SCHENECTADY COUNTY (SCH)

LOC I-SCH	APP CRS		
109.7	040°	Rwy Idg	7001
		TDZE	338
		Apt Elev	378

T NA — Circling Rwy 10 NA at night. Inop table does not apply to S-ILS 4. For inop MALSR, increase S-LOC 4 Cat A/B visibility to 1 mile and Cat C/D visibility to 1⅜ mile. For inoperative MALSR when using Albany altimeter setting, increase S-LOC 4 Cat A/B visibility to 1mile. When using Albany altimeter setting inoperative table does not apply to S-ILS-4. ADF required. When local altimeter setting not received, use Albany altimeter setting and increase all DA 33 feet, and all MDA 40 feet. Helicopter visibility reduction below ¾ SM NA.

MALSR

MISSED APPROACH: Climb to 1500 on 040° course and on HEU NDB bearing 045° then climbing right turn to 3700 direct HEU NDB and hold, continue climb-in-hold to 3700.

AWOS-3	ALBANY APP CON	SCHENECTADY TOWER ★	GND CON	UNICOM
119.275	132.825 263.075	121.3 (CTAF) L 321.1	121.9	122.95

ALTERNATE MISSED APCH FIX

ALBANY ALB 115.3 Chan 100

R-283 103° 283°

HUNTER 356 HEU

HEU 225°

HEU 038°

045°

040°

R-293

R-273

293°

3600

(8.1)

(IAF) HANLY OM/INT

LOCALIZER 109.7 I-SCH

(CFBMK)

BUMPS INT

265°

085°

220°

ALBANY 115.3 ALB Chan 100

MSA HEU 25 NM 3700

839 742 505± 1449 875± 1659 982 688± 1687 1122 2294 1934

HANLY OM/INT

Remain within 10 NM

220°

BUMPS INT

3600

3100

040°

2010

*2000

GS 3.00° TCH 55

3100

3.5 NM 5.1 NM

1500	040° crs	HEU 045°	3700	HEU

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 51).

* LOC only.

ELEV 378 TDZE 338

REIL Rwy 28

HIRL Rwy 4-22 L

MIRL Rwy 10-28 L

22 10 28

7001 X 150

0.9% UP

4850 X 150

TWR 389

040°

CATEGORY	A	B	C	D
S-ILS 4	538-¾ 200 (200-¾)			
S-LOC 4	820-¾ 482 (500-¾)		820-1 482 (500-1)	
CIRCLING	880-1 502 (600-1)	940-1 562 (600-1)	1120-2¼ 742 (800-2¼)	1320-3 942 (1000-3)

FAF to MAP 5.1 NM

Knots	60	90	120	150	180
Min:Sec	5:06	3:24	2:33	2:02	1:42

NE-2, 28 NOV 2024 to 26 DEC 2024
NE-2, 28 NOV 2024 to 26 DEC 2024