

18200

RANGE TWO (RNAV) DEPARTURE (RANGE2•TPH)

TONOPAH TEST RANGE (KTNX)

SHL-3188 [USAF]


TONOPAH, NEVADA

GND CON
 127.25 335.5
 SILVERBOW TOWER ★
 124.75 257.95
 NELLIS CONTROL
 119.35 254.4

Rwy	Knots	60	120	180	240	300	360
14 (A)	V/V(fpm)	205	410	615	820	1025	1230
32 (B)	V/V(fpm)	260	520	780	1040	1300	1560
32 (C)	V/V(fpm)	263	526	789	1052	1315	1578

MINIMUM CLIMB RATE

- (A) to 7500
- (B) to 5900
- (C) to 10,000

TONOPAH
 TPH
 L-9, H-3

10,000

8840

6500

321°

5673

7498

6158

6500

For use by E/F/G and R (RNP 2.0)
 equipped A/C only.

GPS REQUIRED

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RWY 14: Climb heading 141°. When leaving 6500 turn left direct TPH VORTAC, cross TPH at or above 10,000.

TAKE-OFF RWY 32: Climb heading 321°. When leaving 6500 turn left direct TPH VORTAC, cross TPH at or above 10,000.

RANGE TWO (RNAV) DEPARTURE (RANGE2•TPH)

TONOPAH, NEVADA

TONOPAH TEST RANGE (KTNX)