

WAAS CH <b>72834</b> <b>W19A</b>	APP CRS <b>191°</b>	Rwy Idg <b>5001</b> TDZE <b>221</b> Apt Elev <b>221</b>
--	------------------------	---


# RNAV (GPS) RWY 19

PANOLA COUNTY (PMU)

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).  
**▲ NA** DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Oxford altimeter setting.  
 When local altimeter setting not received, use Oxford altimeter setting and increase LPV DA to 571, LNAV/VNAV DA to 1116 and all MDA 80 feet, increase LPV all Cats visibility 3/8 mile, LNAV/VNAV all Cats visibility 1/2 mile, LNAV Cat B visibility 1/4 mile, LNAV Cats C, D visibility 1/2 mile, and Circling Cats B, C visibility 1/4 mile. Rwy 19 helicopter visibility reduction below 3/4 SM NA.



**MISSED APPROACH:**  
 Climb to 1100 then climbing left turn to 2800 direct SUBOY and hold.

AWOS-3PT <b>118.225</b>	MEMPHIS CENTER <b>128.5 279.55</b>	UNICOM <b>122.8 (CTAF) 0</b>
----------------------------	---------------------------------------	---------------------------------



ELEV <b>221</b>	TDZE <b>221</b>
-----------------	-----------------

1100 2800 SUBOY  
 ↑ ↪ ✦  
 VGSI and RNAV glidepath not coincident (VGSI Angle 4.00/TCH 45).  
 4 NM Holding Pattern



CATEGORY	A	B	C	D
LPV DA		500-7/8	279 (300-7/8)	
LNAV/VNAV DA		1045-3	824 (900-3)	
LNAV MDA	940-1	719 (800-2)	940-2	719 (800-2)
<b>C</b> CIRCLING	940-1 719 (800-1)	1000-1 779 (800-1)	1000-2 1/4 779 (800-2 1/4)	1120-3 899 (900-3)

SC-4, 28 NOV 2024 to 26 DEC 2024

SC-4, 28 NOV 2024 to 26 DEC 2024