ILS or LOC RWY 18R

CHARLOTTE/DOUGLAS INTL (CLT)

LOC/DME I-RGS	APP CRS	Rwy Idg	9000
110.15	183°	TDZE	744
Chan 38 (Y)		Apt Elev	748

RADAR required for procedure entry. DME or RADAR required.

Simultaneous approach authorized. CILOV minimums: For inop ALS, increase S-LOC 18R all Cats visibility to RVR 4500.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 on CLT VOR/DME R-250 to STULL INT/CLT 13 DME and hold, continue climb-in-hold to 4000.

D-ATIS	CHARLOTTE APP CON		CHARLOTTE TOWER		GND CON	CLNC DEL
ARR 121.15	(001°-119°)	128.32	(Rwys 18L-36R)	118.1 257.8	121.8 348.6 (WEST)	127.15
DEP 132.1	(120°-295°)	120.05	(Rwy 18C-36C)	126.4 257.8	121.9 348.6 (EAST)	348.6
	(296°-360°)	134.75	(Rwy 18R-36L)	133.35 257.8		CPDLC
	(180°-359°)	257.2				
	(360°-179°)	307.8				







HIRL all Rwys
REIL Rwys 18L and 23
TDZ/CL Rwys 18R, 36L, 36C and 36R

CATEGORY	A	B	C	D
S-ILS 18R	944/18 200 (200-½)			
S-LOC 18R	1200/24 456 (500-½)		1200/45 456 (500-⅞)	
CILOV FIX MINIMUMS (DME REQUIRED)				
S-LOC 18R	1040/24 296 (300-½)			

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

SE-2, 26 DEC 2024 to 23 JAN 2025
SE-2, 26 DEC 2024 to 23 JAN 2025