

LOC/DME I-DWWW <b>111.5</b> Chan 52	APP CRS <b>053°</b>	Rwy Idg TDZE Apt Elev	<b>9004</b> <b>931</b> <b>958</b>
---	------------------------	-----------------------------	---

# ILS or LOC RWY 5




DES MOINES INTL (DSM)

**▼** For inop ALS, increase S-LOC 5 Cats C and D visibility to 1 1/2 SM and CEDIP fix minimums Cats C and D visibility to RVR 5500.  
**▲** Autopilot coupled approach NA below 1256 MSL.  
 #RVR 1800 authorized with use of FD or AP or HUD to DA.



**MISSED APPROACH:** Climb to 1600 then climbing right turn to 3000 direct DSM VORTAC then on DSM VORTAC R-254 to MIDDLE INT/DSM 12 DME and hold.

ATIS <b>119.55</b>	DES MOINES APP CON <b>123.9 307.15</b>	DES MOINES TOWER <b>118.3 257.8</b>	GND CON <b>121.9 348.6</b>	CLNC DEL <b>134.15 317.55</b>
-----------------------	---	--	-------------------------------	----------------------------------



CATEGORY	A	B	C	D
S-ILS 5 #	1131/24 200 (200-1/2)			
S-LOC 5	1440/24	509 (500-1/2)	1440/55	509 (500-1)
<b>C</b> CIRCLING	1440-1	482 (500-1)	1600-1 3/4 642 (700-1 3/4)	1760-2 1/2 802 (900-2 1/2)
CEDIP FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 5	1300/24	369 (400-1/2)	1300/35	369 (400-3/4)
<b>C</b> CIRCLING	1420-1	462 (500-1)	1600-1 3/4 642 (700-1 3/4)	1760-2 1/2 802 (900-2 1/2)