RNAV (GPS) RWY 1L
GENERAL MITCHELL INTL (MKE)

WAAS CH 45742 W01A	APP CRS 011°	Rwy Idg 9080 TDZE 704 Apt Elev 728

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS increase LNAV/VNAV all Cats visibility to RVR 6000, increase LNAV Cat C/D visibility to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1130 then climbing left turn to 2900 direct BAE VOR/DME and hold.

D-ATIS	MILWAUKEE APP CON	MILWAUKEE TOWER	GND CON	CLNC DEL	CPDLC
126.4	126.5 307.0	124.575 269.05	121.8 263.125	120.8	





CATEGORY	A	B	C	D
LPV DA	904/18 200 (200-½)			
LNAV/VNAV DA	1120/40 416 (400-¾)			
LNAV MDA	1120/24 416 (400-½)		1120/40 416 (400-¾)	
C CIRCLING	1240-1 512 (600-1)		1240-1½ 512 (600-1½)	1360-2 632 (700-2)



EC-3, 26 DEC 2024 to 23 JAN 2025
EC-3, 26 DEC 2024 to 23 JAN 2025