

# MERLOT THREE DEPARTURE

AL-281 (FAA)

NAPA COUNTY (APC)  
NAPA, CALIFORNIA

OAKLAND CENTER  
127.8 353.5  
ATIS  
124.05  
CLNC DEL  
127.85  
GND CON  
121.7  
NAPA TOWER★  
118.7 (CTAF) 257.8

**TOP ALTITUDE:  
ASSIGNED BY ATC**

### TAKEOFF MINIMUMS

Rwy 1L: Standard with minimum climb of 420' per NM to 2900.  
Rwy 1R: Standard with minimum climb of 460' per NM to 3000.  
Rwy 6: Standard with minimum climb of 430' per NM to 1600.  
Rwy 19L: Standard with minimum climb of 320' per NM to 1500.  
Rwy 19R: Standard with minimum climb of 330' per NM to 1600.  
Rwy 24: Standard with minimum climb of 255' per NM to 1300.

RED BLUFF  
115.7 RBL  
Chan 104

WILLIAMS  
114.4 IIA  
Chan 91

MENDOCINO  
112.3 ENI  
Chan 70

SACRAMENTO  
115.2 SAC  
Chan 99

SCAGGS ISLAND  
112.1 SGD  
Chan 58

LINDEN  
114.8 LIN  
Chan 95

POINT REYES  
113.7 PYE  
Chan 84

CONCORD  
117.0 CCR  
Chan 117

SAUSALITO  
116.2 SAU  
Chan 109

OAKLAND  
116.8 OAK  
Chan 115

SW-2, 26 DEC 2024 to 23 JAN 2025

SW-2, 26 DEC 2024 to 23 JAN 2025

(CONTINUED ON FOLLOWING PAGE)

NOTE: RADAR required.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 1L/R: Climb on heading 006° (or climbing left turn on ATC assigned heading 186° CW 006°); thence. . . .

TAKEOFF RUNWAY 6: Climbing right turn on assigned heading between 130° CW 242°; thence. . . .

TAKEOFF RUNWAYS 19L/R: Climb on heading 186° (or ATC assigned heading 130° CW 270°); thence. . . .

TAKEOFF RUNWAY 24: Climb on heading 242° (or ATC assigned heading 130° CW 270°); thence. . . .

. . . . expect vectors to join assigned route. Maintain ATC assigned altitude; expect filed altitude/flight level ten minutes after departure.

LOST COMMUNICATIONS

If not in contact with Oakland Center after reaching 4000, proceed to the SGD VORTAC and hold.

SW-2, 26 DEC 2024 to 23 JAN 2025

SW-2, 26 DEC 2024 to 23 JAN 2025