

# TAMPA SEVEN DEPARTURE

**TOP ALTITUDE:  
3000**

SEMINOLE  
117.5 SZW  
Chan 122

TAYLOR  
112.9 TAY  
Chan 76

CROSS CITY  
112.0 CTY  
Chan 57

OCALA  
113.7 OCF  
Chan 84

GATORS  
116.2 GNV  
Chan 109

D-ATIS DEP  
128.475  
CLNC DEL  
133.6  
CPDLC  
GND CON  
121.7 269.4  
TAMPA TOWER  
119.5 269.4  
TAMPA DEP CON  
134.25 279.6

△  
COVIA

ST PETERSBURG  
116.4 PIE  
Chan 111

SARASOTA  
117.0 SRQ  
Chan 117

ORLANDO  
112.2 ORL  
Chan 59

LAKELAND  
116.0 LAL  
Chan 107

PAHOKEE  
115.4 PHK  
Chan 101

LEE COUNTY  
114.15 RSW  
Chan 88(Y)

NOTE: Turboprops/Props only.  
NOTE: RADAR required.

**TAKEOFF MINIMUMS:**

Rwys 11/R, 19R, 28: Standard.

Rwy 10: Standard with minimum climb of 245' per NM to 900.

Rwy 19L: 200-1½ or standard with minimum climb of 220' per NM to 300, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1500' prior to departure end of runway.

NOTE: Chart not to scale.



## DEPARTURE ROUTE DESCRIPTION

**TAKEOFF RUNWAYS 11L/R:** Climb heading 007°, thence. . . .

**TAKEOFF RUNWAY 10:** Climb heading 097°, thence. . . .

**TAKEOFF RUNWAYS 19L/R:** Climb heading 187° to cross PIE R-116 at or above 2600, thence. . . .

**TAKEOFF RUNWAY 28:** Climb heading 277°, thence. . . .

. . . .expect RADAR vectors to join filed/assigned route. Maintain 3000. Expect clearance to filed altitude/flight level within 10 minutes after departure.