RNAV (GPS) RWY 4

TUSCALOOSA NTL (TCL)

WAAS CH 48906 W04A	APP CRS 041°	Rwy Idg 6498 TDZE 160 Apt Elev 170

RNP APCH - GPS.

Circling Rwy 12 , 30 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -7°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to 1⅛ SM.

MALSR

MISSED APPROACH: Climb to 2500 direct NENMY and on track 125° to OKW VORTAC and hold.

ASOS	BIRMINGHAM APP CON	TUSCALOOSA TOWER ★	GND CON	CLNC DEL	UNICOM
132.825	120.15 269.25	126.3 (CTAF) L 256.7	121.8 257.95	120.775	122.95





CATEGORY	A	B	C	D
LPV DA		360-½	200 (200-½)	
LNAV/VNAV DA		575-¾	415 (500-¾)	
LNAV MDA	600-½ 440 (500-½)		600-¾ 440 (500-¾)	
C CIRCLING	720-1 550 (600-1)	800-1 630 (700-1)	960-2¼ 790 (800-2¼)	960-2½ 790 (800-2½)



SE-4, 26 DEC 2024 to 23 JAN 2025