RNAV (GPS) RWY 15

AURORA MUNI (ARR)

WAAS	APP CRS	Rwy ldg	5503
CH 72941	148°	TDZE	712
W15A		Apt Elev	712

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Rwy 15 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct UQITY and hold, continue climb-in-hold to 3000.

ATIS	CHICAGO APP CON	AURORA TOWER★	GND CON	CLNC DEL	UNICOM
125.85	133.5 349.0	120.6 (CTAF) L	121.7	121.7 (When tower closed)	122.95 123.5





CATEGORY	A	B	C	D
LPV DA	962-¾ 250 (300-¾)			
LNAV/VNAV DA	962-¾ 250 (300-¾)			
LNAV MDA	1260-1 548 (600-1)		1260-1⅝ 548 (600-1⅝)	
C CIRCLING	1260-1 548 (600-1)		1300-1⅝ 588 (600-1⅝)	1320-2 608 (700-2)



HIRL Rwys 15-33 and 9-27 L
MIRL Rwys 18-36 L
REIL Rwys 15, 18, 27, and 36 L

EC-3, 26 DEC 2024 to 23 JAN 2025
EC-3, 26 DEC 2024 to 23 JAN 2025