


WAAS CH <b>78040</b> <b>W18A</b>	APP CRS <b>181°</b>	Rwy Idg TDZE Apt Elev	<b>3672</b> <b>819</b> <b>824</b>
--	------------------------	-----------------------------	---

# RNAV (GPS) RWY 18

PORTAGE MUNI (C47)



RNP APCH - GPS.	MISSED APPROACH: Climbing left turn to 2600 direct HOPES and hold.
<p>▼ Rwy 18 helicopter visibility reduction below 1 SM NA. ▲ NA Procedure NA at night. Use Baraboo altimeter setting.</p>	

DLL AWOS-3 <b>118.325</b>	MADISON APP CON ★ <b>135.45 343.7</b>	UNICOM <b>122.7 (CTAF)</b>
------------------------------	--	-------------------------------



EC-3, 26 DEC 2024 to 23 JAN 2025

EC-3, 26 DEC 2024 to 23 JAN 2025



CATEGORY	A	B	C	D
LP MDA	1260-1	441 (500-1)	1260-1 <sup>3</sup> / <sub>8</sub> 441 (500-1 <sup>3</sup> / <sub>8</sub> )	NA
LNAV MDA	1320-1	501 (500-1)	1320-1 <sup>3</sup> / <sub>8</sub> 501 (500-1 <sup>3</sup> / <sub>8</sub> )	NA
<b>C</b> CIRCLING	1420-1	596 (600-1)	1640-2 <sup>1</sup> / <sub>2</sub> 816 (900-2 <sup>1</sup> / <sub>2</sub> )	NA