

HOODO SEVEN DEPARTURE (RNAV)

SC-5, 26 DEC 2024 to 23 JAN 2025

ASOS 119.925
CLNC DEL 125.2
CTAF 123.0
HOUSTON DEP CON 134.45 284.0


NOTE: RNAV 1.

NOTE: RADAR required.

NOTE: ATC assigned only.

NOTE: DME/DME/IRU or GPS required.

NOTE: For non-GPS equipped aircraft, LCH, LLA, TBD, and LEV DME's must be operational.



SCHOLES VUH



118° (32)

HOODO

11000 *1400

087° (36)

SBIRD

(60)

CFOOD

(68)

BOWFN

076° (60)

11000 *1700

LEEVILLE LEV

048° (82)

11000 *1000

HARVEY HRV

1000

TAKEOFF MINIMUMS

Rwys 17, 35: Standard with minimum climb of 500' per NM to 540.

TOP ALTITUDE: ASSIGNED BY ATC

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 17: Climb on heading 175° to 540, for RADAR vectors to VUH VOR/DME, thence

TAKEOFF RUNWAY 35: Climb on heading 355° to 540, for RADAR vectors to VUH VOR/DME, thence

. on track 118° to HOODO, then on (transition). Maintain ATC assigned altitude.
Expect filed altitude 10 minutes after departure.

BOWFN TRANSITION (HOODO7.BOWFN)

CFOOD TRANSITION (HOODO7.CFOOD)

HARVEY TRANSITION (HOODO7.HRV)

LEEVILLE TRANSITION (HOODO7.LEV)

SBIRD TRANSITION (HOODO7.SBIRD)

SC-5, 26 DEC 2024 to 23 JAN 2025