

RADAR MINS

24277

N1

RADAR INSTRUMENT APPROACH MINIMUMS

BELLEVILLE, IL

Orig-A, 08SEP22 (22251) (FAA)

ELEV 459

SCOTT AFB / MIDAMERICA ST LOUIS (BLV)

RADAR-1 125.2 281.5 **▽ ▲**

| | <u>RWY</u> | <u>GP/TCH/RPI</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> |
|-------------------|------------|-------------------|------------|------------------------------|---------------------------|-----------------|------------|------------------------------|---------------------------|-----------------|
| ASR | 32L | | AB | 880/24 | 441 | (500-½) | CDE | 880/45 | 441 | (500-¾) |
| | 32R | | AB | 920/24 | 478 | (500-½) | CDE | 920/50 | 478 | (500-1) |
| | 14L | | AB | 1020/55 | 578 | (600-1) | CDE | 1020-1% | 578 | (600-1½) |
| | 14R | | AB | 1100/24 | 641 | (700-½) | CDE | 1100-1% | 641 | (700-1¾) |
| C CIRCLING | ALL RWY | | A | 1100-1 | 641 | (700-1) | B | 1120-1 | 661 | (700-1) |
| | | | C | 1240-2¼ | 781 | (800-2¼) | D | 1240-2½ | 781 | (800-2½) |
| | | | E | 1240-2¾ | 781 | (800-2¾) | | | | |

Inoperative table does not apply to S-14L all Cats.

For inoperative ALS, increase S-14R CAT E visibility to 1½ mile.

For inoperative ALS, increase S-32L CAT E visibility to 1½ mile.

For inoperative ALS, increase S-32R CATs C, D, E visibility to 1½ mile.

Rwy 14L helicopter visibility reduction below RVR 4000 not authorized.

CHAMPAIGN/URBANA, IL Amdt 6C, 12NOV15 (22027) (FAA)

ELEV 755

UNIVERSITY OF ILLINOIS/WILLARD (CMI) **▲**

RADAR-1 (319°-138°) 121.35 285.65 (139°-318°) 132.85 290.225

| | <u>RWY</u> | <u>GP/TCH/RPI</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> |
|----------|------------|-------------------|------------|------------------------------|---------------------------|-----------------|------------|------------------------------|---------------------------|-----------------|
| ASR | 32R | | ABC | 1180/40 | 430 | (500-¾) | D | 1180/50 | 430 | (500-1) |
| | 14L | | AB | 1200-1 | 445 | (500-1) | CD | 1200-1% | 445 | (500-1¾) |
| CIRCLING | ALL RWY | | AB | 1240-1 | 485 | (500-1) | C | 1500-2¼ | 745 | (800-1¼) |
| | | | D | 1500-2½ | 745 | (800-2½) | | | | |

When control tower closed ASR and alternate minimums NA.

CHICAGO/ROCKFORD, IL Amdt 11, 05SEP24 (24277) (FAA)

ELEV 742

CHICAGO/ ROCKFORD INTL (RFD)

RADAR-1 121.0 327.0 **▽ ▲**

| | <u>RWY</u> | <u>GP/TCH/RPI</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> | <u>CAT</u> | <u>DA/</u> <u>MDA-VIS</u> | <u>HAT/</u> <u>HAA</u> | <u>CEIL-VIS</u> |
|-------------------|------------|-------------------|------------|------------------------------|---------------------------|-----------------|------------|------------------------------|---------------------------|-----------------|
| ASR | 1 | | AB | 1180/24 | 451 | (500-½) | CD | 1180/45 | 451 | (500-¾) |
| | 7 | | AB | 1220/24 | 478 | (500-½) | CD | 1220/50 | 478 | (500-1) |
| | 25 | | AB | 1200/55 | 464 | (500-1) | CD | 1200-1% | 464 | (500-1¾) |
| C CIRCLING | ALL RWY | | A | 1220-1 | 478 | (500-1) | B | 1280-1 | 538 | (600-1) |
| | | | C | 1320-1½ | 578 | (600-1½) | D | 1460-2¼ | 718 | (800-2¼) |

Rwy 25 helicopter visibility reduction below ¾ SM not authorized.

For inoperative ALS, increase S-7 Cat C and D visibility to 1½ SM.

EC-3

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

24277

N1

26 DEC 2024 to 23 JAN 2025

26 DEC 2024 to 23 JAN 2025

RADAR MINS

24277

N2

RADAR INSTRUMENT APPROACH MINIMUMS

GREEN BAY, WI

Amdt 9F, 24MAR22 (22083) (FAA)

ELEV 695

GREEN BAY/AUSTIN STRAUBEL INTL (GRB)

RADAR-1 119.4 338.2 **▽ ▲**

| | <u>RWY</u> | <u>GP/TCH/RPI</u> | <u>CAT</u> | <u>DA/ MDA-VIS</u> | <u>HAT/ HAA</u> | <u>CEIL-VIS</u> | <u>CAT</u> | <u>DA/ MDA-VIS</u> | <u>HAT/ HAA</u> | <u>CEIL-VIS</u> |
|----------|------------|-------------------|------------|------------------------|---------------------|-----------------|------------|------------------------|---------------------|-----------------|
| ASR | 36 | | AB | 1100/24 | 418 | (500-½) | C | 1100/40 | 418 | (500-¾) |
| | | | D | 1100/50 | 418 | (500-1) | | | | |
| | 24 | | AB | 1140-1 | 458 | (500-1) | C | 1140-1¾ | 458 | (500-1¾) |
| | | | D | 1140-1½ | 458 | (500-1½) | | | | |
| | 6 | | AB | 1220/24 | 528 | (600-½) | C | 1220/50 | 528 | (600-1) |
| | | | D | 1220/60 | 528 | (600-1¼) | | | | |
| 18 | | AB | 1220-1 | 525 | (600-1) | C | 1220-1½ | 525 | (600-1½) | |
| | | D | 1220-1¾ | 525 | (600-1¾) | | | | | |
| CIRCLING | ALL RWY | | AB | 1220-1 | 525 | (600-1) | C | 1300-1¾ | 605 | (700-1¾) |
| | | | D | 1300-2 | 605 | (700-2) | | | | |

For inoperative MALSR, increase ASR S-36 Category D visibility to RVR 6000.
When control tower closed, ASR not authorized.

SPRINGFIELD, IL

Amdt 9C, 17JUN21 (22251) (FAA)

ELEV 598

ABRAHAM LINCOLN CAPITAL (SPI)

RADAR-1 126.15 323.0 **▽ ▲**

| | <u>RWY</u> | <u>GP/TCH/RPI</u> | <u>CAT</u> | <u>DA/ MDA-VIS</u> | <u>HAT/ HAA</u> | <u>CEIL-VIS</u> | <u>CAT</u> | <u>DA/ MDA-VIS</u> | <u>HAT/ HAA</u> | <u>CEIL-VIS</u> |
|----------|------------|-------------------|------------|------------------------|---------------------|-----------------|------------|------------------------|---------------------|-----------------|
| ASR | 4 | | ABC | 1060/24 | 472 | (500-½) | DE | 1060/50 | 472 | (500-1) |
| | | | | | | | | | | |
| | 22 | | AB | 1100-½ | 502 | (600-½) | CDE | 1100-1 | 502 | (600-1) |
| 31 | | | | AB | 1240-½ | 650 | (700-1) | C | 1240-1¼ | 650 |
| | D | 1240-1½ | | 650 | (700-1½) | E | 1240-1¾ | 650 | (700-1¾) | |
| CIRCLING | ALL RWY | | AB | 1240-1 | 642 | (700-1) | C | 1360-2¼ | 762 | (800-2¼) |
| | | | D | 1380-2½ | 782 | (800-2½) | E | 1380-2¾ | 782 | (800-2¾) |

When local altimeter setting not received, use Lincoln altimeter setting and increase all MDAs 60 feet and increase S-22 visibility CATs C/D/E ¼ SM, S-4 visibility CAT C ¼ SM and Circling visibility CATs C/D/E ¼ SM.

For inoperative MALSR increase S-4 CATs D and E visibility to 1½ mile.

When control tower closed, ASR not authorized.

26 DEC 2024 to 23 JAN 2025

26 DEC 2024 to 23 JAN 2025

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

24277

N2

EC-3