ILS Z or LOC Z RWY 10R

CHICAGO O'HARE INTL (ORD)

LOC/DME I-IZJ	APP CRS	Rwy Idg	7500
110.75	094°	TDZE	680
Chan 44 (Y)		Apt Elev	680

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.
Simultaneous approach authorized.
For inop ALS, increase S-LOC 10R Cat C and D visibility to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS	CHICAGO APP CON	O'HARE TOWER	GND CON	(TWR CENTER)	CLNC DEL	CPDLC
135.4 282.225	119.0 292.125	133.0 348.0	124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	121.75 (OBND) 121.9 (IBND)	121.6	

ALTERNATE MISSED APCH FIX
JOLIET
JOT
112.3
Chan 70
R-246-066° 246°

MSA ORD 25 NM
3400
113.0 OBK Chan 77
113.0 OBK R-185 Chan 77
R-196

(IAF) GIBNS
SAFLY I-IZJ 27.7 RADAR
POPOF I-IZJ 24.6 RADAR
DAYZE I-IZJ 21.4 RADAR
BNITO I-IZJ 18.3 RADAR
(IF) BOOTR I-IZJ 15.2 RADAR
NIRRA I-IZJ 12 RADAR
KUULA INT I-IZJ 6.5 RADAR
ALYEA INT I-IZJ 3.4 RADAR
IM

8000 7000 6000 5000 4000 2300
094° (3.1) (3.1) (3.1) (3.1) (3.2) 094° (5.5)
274°
9000
087° (20.2)
1468 883 813 834 1185 1508

R-248 068° 248°
DUPAGE
108.4 DPA
Chan 21

LOCALIZER 110.75
I-IZJ
Chan 44 (Y)

EC-3, 23 JAN 2025 to 20 FEB 2025

EC-3, 23 JAN 2025 to 20 FEB 2025

1200 4000 DPA

*LOC only

9000 8000 7000 6000 5000 4000 2300 *1220
094°
GS 3.00°
TCH 55
*I-IZJ 2.7
I-IZJ 1.6
IM

3.1 NM | 3.1 NM | 3.1 NM | 3.1 NM | 3.2 NM | 5.5 NM | 3.1 NM | 0.7 | 1 NM | 0.1

CATEGORY	A	B	C	D
S-ILS 10R	880/18 200 (200-½)			
S-LOC 10R	1100/24 420 (500-½)			

ELEV 680 D TDZE 680

7500 X 150
TWR 914
7500 X 150
0.3% DOWN
11245 X 200
11260 X 150
TWR 910
13000 X 150
0.3% DOWN
10800 X 200
TWR 876
0.3% UP
7500 X 150
0.3% DOWN
094°

HIRL all Rwys
TDZ/CL all Rwys except 4L

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38