TACAN RWY 12R

VORTAC STL	APCH CRS	Rwy ldg 10,552
117.4	142°	TDZE 540
Chan 121		Arpt Elev 618

AL-360 [USAF]

ST. LOUIS LAMBERT INTL (KSTL)

* Inoperative table does not apply.

NA Visibility reduction by helicopters NA

MALSR

MISSED APPROACH: Climb to 1500 then climbing left turn to 5000 intercept STL R-128 to FONTI INT/STL 22.4 DME and hold, continue climb in hold.

ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CLNC DEL
125.025 379.925	121.02 338.25	N 120.05 284.6 / W 132.475 239.275 / S 118.5 257.7	(Inbd) 121.9 348.6 (Outbd) 121.65 377.175 (West) 118.925 227.125	119.5 363.1



ELEV 618 TDZE 540



CATEGORY	A	B	C	D	E
S-12R *	1060/50 520 (500-1)		1060-1½ 520(500-1½)	1060-1¾ 520 (500-1¾)	
CIRCLING	NOT AUTHORIZED				

Rwy 6-24 7607 x 150
Rwy 11-29 9001 x 150
Rwy 12L-30R 9003 x 150
Rwy 12R-30L 11,019 x 200
Rwy 12R ldg 10,552′
Rwy 30L ldg 10,818′



38°45′N-90°22′W

TACAN RWY 12R

NC-3, 23 JAN 2025 to 20 FEB 2025

NC-3, 23 JAN 2025 to 20 FEB 2025