

WAAS CH 81819	APP CRS 044°	Rwy Idg 8400 TDZE 12 Apt Elev 13
-------------------------	------------------------	---

RNAV (GPS) Y RWY 4R

JOHN F KENNEDY INTL (JFK)

RNP APCH.


Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cat C/D visibility to 1 1/2 SM.

ALSF-2



MISSED APPROACH: (Do not exceed 210K until GAALO) Climb to 4000 direct GAALO and on track 083° to HIRBO and hold.

D-ATIS (ARR/DEP) (ARR-NE) (ARR-SW) 128.725 117.7 115.4	NEW YORK APP CON 128.125 269.0	KENNEDY TOWER Rwys 4R/22L and 13L/31R 119.1 281.55 Rwys 4L/22R and 13R/31L 123.9 281.55	GND CON 121.9 348.6	CLNC DEL 135.05 348.6	CPDLC
---	--	---	-------------------------------	---------------------------------	-------



NE-2, 23 JAN 2025 to 20 FEB 2025

NE-2, 23 JAN 2025 to 20 FEB 2025

ELEV 13	D TDZE 12
---------	------------------

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 69).		4000	GAALO	HIRBO
VERRU		↑	✧	✧
*LNAV only		fr 083°		
GP 3.00° TCH 53	2000	1500	1500	1500
	044°			
	6 NM	3.1 NM	1.4 NM	
CATEGORY	A	B	C	D
LPV DA		212/18	200 (200-1/2)	
LNAV/VNAV DA		369/40	357 (400-3/4)	
LNAV MDA	520/24	508 (600-1/2)	520/55	508 (600-1)
C CIRCLING	640-1	627 (700-1)	680-1 3/4 667 (700-1 3/4)	680-2 667 (700-2)

