RNAV (GPS) RWY 5

WAUKEGAN NTL (UGN)

WAAS	APP CRS	Rwy Idg	6001
CH 81812	051°	TDZE	726
W05A		Apt Elev	728

RNP APCH - GPS.

Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling Rwy 14, 32 NA at night.

MISSED APPROACH: Climb to 2300 direct LIRIC and hold.

ATIS	CHICAGO APP CON	WAUKEGAN TOWER ★	GND CON
132.4	120.55	120.05 (CTAF) L 273.55	121.65





CATEGORY	A	B	C	D
LPV DA	976-¾ 250 (300-¾)			
LNAV/VNAV DA	1013-⅞ 287 (300-⅞)			
LNAV MDA	1120-1 394 (400-1)		1120-1⅛ 394 (400-1⅛)	
C CIRCLING	1220-1 492 (500-1)		1220-1½ 492 (500-1½)	1400-2¼ 672 (700-2¼)

ELEV 728 TDZE 726



REIL Rwy 5 L
HIRL Rwy 5-23 L
MIRL Rwy 14-32 L

EC-3, 23 JAN 2025 to 20 FEB 2025
EC-3, 23 JAN 2025 to 20 FEB 2025