

WAAS CH <b>86525</b> <b>W32A</b>	APP CRS <b>321°</b>	Rwy ldg <b>5507</b> TDZE <b>996</b> Apt Elev <b>998</b>
--	------------------------	---

# RNAV (GPS) RWY 32


NEW RICHMOND RGNL (R.NH)

RNP APCH.



**⚠** Baro-VNAV NA when using Osceola altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 37°C (98°F). Rwy 32 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Osceola altimeter setting and increase all DA/MDA 40 feet; increase LNAV visibility Cats C and D ½ SM and Circling Cats C and D ¼ SM. Circling to Rwy 4, 22 NA.

**⚠** MISSED APPROACH: Climb to 3500 direct ENEPE and hold.

AWOS-3 <b>120.0</b>	MINNEAPOLIS APP CON <b>121.2 335.65</b>	GCO <b>121.725</b>	UNICOM <b>122.975 (CTAF) 0</b>
------------------------	--	-----------------------	-----------------------------------



ELEV 998	TDZE 996
----------	----------



CATEGORY	A	B	C	D
LPV DA		1246-1	250 (300-1)	
LNAV/VNAV DA		1295-1	299 (300-1)	
LNAV MDA	1420-1	424 (500-1)	1420-1¼	424 (500-1¼)
<b>C</b> CIRCLING	1540-1	542 (600-1)	1660-1¾ 662 (700-1¾)	1660-2 662 (700-2)

EC-3, 23 JAN 2025 to 20 FEB 2025

EC-3, 23 JAN 2025 to 20 FEB 2025