

LOC I-GBI 108.5	APP CRS 055°	Rwy Idg TDZE Apt Elev	7569 708 727
---------------------------	------------------------	-----------------------------	---

ILS or LOC RWY 5

BUFFALO NIAGARA INTL (BUF)




RADAR required for procedure entry. RNP APCH - GPS. ADF required for LOC only.

Autopilot coupled approach NA. For inop ALS, increase S-LOC 5 Cats C and D visibility to RVR 5500.



MISSED APPROACH: Climb to 3000 direct TRAVA and hold.

D-ATIS 135.35	BUFFALO APP CON 126.15 263.125	BUFFALO TOWER 120.5 257.8	GND CON 133.2 257.8	CLNC DEL 124.7 257.8	CPDLC
-------------------------	--	-------------------------------------	-------------------------------	--------------------------------	-------



CATEGORY	A	B	C	D
S-ILS 5	908/18 200 (200-½)			
S-LOC 5	1060/24	352 (400-½)	1060/30	352 (400-¾)
CIRCLING	1200-1	473 (500-1)	1220-1½	1340-2
			493 (500-1½)	613 (700-2)

NE-2, 20 FEB 2025 to 20 MAR 2025

NE-2, 20 FEB 2025 to 20 MAR 2025