

(LGRHD3.LGRHD) 23110

AL-76 (FAA)

CHARLESTON AFB/INTL (CHS)
CHARLESTON, SOUTH CAROLINA

LGRHD THREE DEPARTURE (RNAV)

D-ATIS
124.75
CLNC DEL
127.325 291.65
CPDLC
GND CON
121.9 348.6
CHARLESTON TOWER
126.0 239.0
CHARLESTON DEP CON
120.7 306.925

**TOP ALTITUDE:
4000**

TAKEOFF MINIMUMS

Rwys 15, 33: Standard.
Rwys 3, 21: Standard with minimum
climb of 500' per NM to 560.

- NOTE: If unable to accept climb rate, advise ATC on initial contact.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.
- NOTE: RADAR required for non-GPS equipped aircraft.
- NOTE: For non-GPS equipped aircraft: SAV and VAN DMEs must be operational.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb on heading 031° to 560, then left turn direct HALEE, then on depicted route to LGRHD, thence. . . .


TAKEOFF RUNWAY 15: Climb on heading 154° to 560, then right turn direct LGRHD, thence. . . .

TAKEOFF RUNWAY 21: Climb on heading 211° to 560, then direct LGRHD, thence. . . .

TAKEOFF RUNWAY 33: Climb on heading 334° to 560, then left turn direct HALEE, then on depicted route to LGRHD, thence. . . .

. . . . on assigned transition/route, maintain 4000.
Expect clearance to filed altitude/flight level within ten (10) minutes after departure.

GIPPL TRANSITION (LGRHD3.GIPPL):



SE-2, 20 FEB 2025 to 20 MAR 2025

SE-2, 20 FEB 2025 to 20 MAR 2025

LGRHD THREE DEPARTURE (RNAV)
(LGRHD3.LGRHD) 05NOV20

CHARLESTON, SOUTH CAROLINA
CHARLESTON AFB/INTL (CHS)