

WAAS CH 60911 W16B	APP CRS 163°	Rwy Idg TDZE Apt Elev	9010 570 608
--	------------------------	-----------------------------	---

RNAV (GPS) Y RWY 16R


SEATTLE PAINE FLD INTL (P.A.E.)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C (23°F) or above 54°C (130°F). Circling Rwy 34R NA at night. DME/DME RNP-0.3 NA. For inop ALS, increase LNAV/VNAV Cats A/B visibility to RVR 5000.

MALSR

MISSED APPROACH: Climb to 1100 then climbing right turn to 2000 direct ECEPO and hold.

ATIS 128.65	SEATTLE APP CON 128.5 306.9	PAINE TOWER ★ 132.95 (CTAF) 0 256.7	GND CON 121.8 339.8	CLNC DEL 127.175	UNICOM 122.95
-----------------------	---------------------------------------	---	-------------------------------	----------------------------	-------------------------



VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 74).				
4 NM Holding Pattern				
EYWOK				
3000 ← 343° 163° →				
GP 3.00° TCH 57				
2000				
ITIPE				
2000				
*1.1 NM to RWY 16R				
RWY 16R				
6.8 NM 3.2 NM 1.1				
CATEGORY	A	B	C	D
LPV DA	770/18	200 (200-½)	NA	
LNAV/VNAV DA	894/30	324 (300-⅝)	NA	
LNAV MDA	1000/24	430 (400-½)	NA	
CIRCLING	1100-1	492 (500-1)	NA	

