RNAV (RNP) Y RWY 18C

MEMPHIS INTL (MEM)

APP CRS	Rwy Idg	11120
180°	TDZE	290
	Apt Elev	341

For uncompensated Baro-VNAV systems, procedure NA below -10°C (14°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.30* all Cats visibility to 1¼ SM and RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 180° to CEDEN on track 137° to KEEZE and hold, continue climb-in-hold to 5000. *Missed approach requires a minimum climb of 400 feet per NM to 1000.

MEMPHIS APP CON		
119.1	291.6	(176°-355°)
125.8	338.3	(356°-175°)

MEMPHIS TOWER		
(Rwy 9-27)	118.3	257.8
(Rwys 18C-36C, 18L-36R)	119.7	257.8
(Rwy 18R-36L)	128.425	257.8

GND CON		
(Rwy 9-27)	121.0	379.2
(Rwys 18C-36C, 18L-36R)	121.9	379.2
(Rwy 18R-36L)	121.65	379.2

D-ATIS 127.75

CLNC DEL 125.2

CPDLC

RADAR REQUIRED

(IF) LAURI

180° (6.1) 2000

1337

1450

(FAF) JALDO

720

180° (5.2)

1001

RW18C

602

506

753

180° (7)

CEDEN 879

137° (6.4)

MSA RW18C 25 NM

2500

MISSED APCH FIX

KEEZE 153° 333° 5 NM

ELEV 341 D TDZE 290

180°

0.3% UP 8946 X 150 0.6% DOWN

TWR 621

TDZ/CL Rwys 18L, 18C, 18R, 36R, 36C, and 36L HIRL all Rwys

0.7% UP 0.8% UP 9000 X 150 0.5% DOWN 0.5% DOWN 9220 X 150 0.6% DOWN

36L 36C 36R

5000	tr 180°	CEDEN	tr 137°	KEEZE

LAURI 3900

JALDO 2000

RW18C

180°

2000

GP 3.00° TCH 54

5.2 NM 6.1 NM

CATEGORY	A	B	C	D
RNP 0.30 DA*	655/35	365 (400-⅝)		
RNP 0.30 DA	747/54	457 (500-1)		

AUTHORIZATION REQUIRED

SE-1, 20 FEB 2025 to 20 MAR 2025
SE-1, 20 FEB 2025 to 20 MAR 2025