


APP CRS	Rwy Idg	7000
278°	TDZE	257
	Apt Elev	257

RNAV (RNP) Z RWY 28L
MONTEREY RGNL (MR.Y)

⚠ For uncompensated Baro-VNAV systems, procedure NA below 0°C (32°F) or above 48°C (120°F). RF required. GPS required.	MISSED APPROACH: Climb to 5500 on track 278° to URUYU, right turn to CUGVU, and on track 101° to SNS VORTAC and hold.
--	--

ATIS 119.25	NORCAL APP CON 133.0 251.15 (001°-135°) 127.15 307.125 (136°-360°)	MONTEREY TOWER★ 118.4(CTAF) 0 257.8	GND CON 120.875 348.6	CLNC DEL 135.45	UNICOM 122.95
----------------	--	--	--------------------------	--------------------	------------------



ELEV 257	D	TDZE 257
MIRL Rwy 10L-28R HIRL Rwy 10R-28L REIL Rwy 28L REIL Rwy 10L and 28R		
5500 URUYU CUGVU tr 101° SNS tr 278°		
SNS VORTAC 5 NM Holding Pattern		
CONIV 4000 034° 214° 4900 HUTAD 1505 2143 214° 4000 OKUPE 2143 214° 4000		
RW28L 278° 3.2 NM 1.7 NM 4.9 NM 4 NM		
GP 3.60° TCH 45		
CATEGORY	A	B C D
RNP 0.10 DA	527/45	270 (300-7%) NA
RNP 0.15 DA	767- 1½	510 (600-1½) NA
RNP 0.20 DA	1236-3	979 (1000-3) NA
AUTHORIZATION REQUIRED		

SW-2, 20 FEB 2025 to 20 MAR 2025

SW-2, 20 FEB 2025 to 20 MAR 2025