SAN ANTONIO, TEXAS

HI-ILS or LOC/DME Z RWY 34

LOC I-OSQ	APCH CRS	Rwy ldg 11,550 / TDZE 660 / Arpt Elev 690
110.7	338°	

[USAF]

KELLY FLD (KSKF)

* When ALS inop, increase RVR to 40 and vis to ¾ mile.
** When ALS inop, increase RVR to 55 and vis to 1 mile.
*** Circling not authorized E of Rwy 16-34.

ALSF-1

MISSED APPROACH: Climbing to 2500 via KSY TACAN R-331 until 9 DME, cross 9 DME at 2500, then continue climb to 3000 to IDEEL/12.0 DME. Expect ATC instructions.

ATIS	SAN ANTONIO APP CON	TOWER	GND CON
120.45 273.5	118.05 353.5	124.3 322.35	121.8 289.4



2500 KSY R-331	KSY R-331 9	3000 IDEEL KSY 12



ELEV 690	TDZE 660



CATEGORY	C	D	E
S-ILS 34 *	860/24	200	(200-½)
S-LOC/DME 34 **	1020/30	360	(400-⅝)
C CIRCLING ***	1340-1¾ 650 (700-1¾)	1400-2¼ 710 (800-2¼)	1900-3 1210 (1300-3)

SAN ANTONIO, TEXAS

29°23'N-98°35'W

KELLY FLD (KSKF)

Amdt 2 13JUN24

HI-ILS or LOC/DME Z RWY 34

SC-3, 20 FEB 2025 to 20 MAR 2025