LOC/DME I-MOT	APP CRS	Rwy Idg	7700
111.9	312°	TDZE	1679
Chan 56		Apt Elev	1716

ILS or LOC RWY 31

MINOT INTL (MOT)

DME or RADAR required.

For Inop ALS, increase S-ILS 31 Cat E visibility to RVR 4000, and S-LOC 31 Cat C, D and E visibility to RVR 4500. Autopilot coupled approach NA below 2500.

MALSR

MISSED APPROACH: Climb to 3700 then left turn direct MOT VOR/DME and hold.

ASOS	MINOT APP CON ★	MAGIC CITY TOWER ★	GND CON	UNICOM
118.725	119.6 363.8	118.2 (CTAF) L 251.125	121.9	122.95







CATEGORY	A	B	C	D	E
S-ILS 31	1879/24 200 (200-½)				
S-LOC 31	1980/24 301 (300-½)			1980/40 301 (300-¾)	
CIRCLING	2200-1 484 (500-1)	2240-1 524 (600-1)	2800-3 1084 (1100-3)		

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

NC-1, 20 FEB 2025 to 20 MAR 2025
NC-1, 20 FEB 2025 to 20 MAR 2025