RNAV (GPS) Y RWY 6

TETERBORO (TEB)

WAAS	APP CRS	Rwy Idg	6013
CH 65707	060°	TDZE	6
W06A		Apt Elev	8

RNP APCH - GPS.
RADAR required.

Circling NA for Cats B, C, and D northwest of Rwys 6 and 19.
For inop ALS, increase LPV all Cats visibility to RVR 5500 and increase LNAV Cats C/D visibility to 2½ SM.

MALSR

MISSED APPROACH: Climb to 1000, then climbing left turn to 2000 direct TEBLE, cross TEBLE at or below 2000, then climb to 3000 on track 272° to UBUCK and hold.

D-ATIS	NEWARK APP CON	TETERBORO TOWER	GND CON	CLNC DEL	CPDLC
114.2 132.85	127.6 379.9	119.5	121.9	128.05	





CATEGORY	A	B	C	D
LPV DA	369/35		363 (400-⅝)	
LNAV MDA	800/24 794 (800-½)	800/40 794 (800-¾)	800-1¾ 794 (800-1¾)	
CIRCLING	800-1 792 (800-1)	800-1¼ 792 (800-1¼)	820-2½ 812 (900-2½)	1040-3 1032 (1100-3)



TDZ/CL Rwys 6 and 19
HIRL Rwys 1-19 and 6-24
REIL Rwys 1, 6, 19 and 24

NE-2, 20 FEB 2025 to 20 MAR 2025
NE-2, 20 FEB 2025 to 20 MAR 2025