

| | | | |
|--|------------------------|-----------------------------|---|
| WAAS CH 86829 W21A | APP CRS 210° | Rwy Idg TDZE Apt Elev | 5204 708 708 |
|--|------------------------|-----------------------------|---|


RNAV (GPS) RWY 21

CLINTON MUNI (CWI)



⚠ Rwy 21 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Davenport altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Davenport altimeter setting: increase all DA 47 feet and all MDA 60 feet. Increase LNAV Cat C visibility ¼ mile.

MISSED APPROACH: Climb to 3000 direct WIKES and on track 234° to CVA VORTAC and hold.

| | | | |
|----------------------------|--|----------------------------|-------------------------------|
| AWOS-3PT 125.525 | QUAD CITY APP CON ★ 125.95 257.8 | CLNC DEL 118.5 0 | UNICOM 122.8 (CTAF) |
|----------------------------|--|----------------------------|-------------------------------|



| | | |
|----------|----------|----------|
| ELEV 708 | D | TDZE 708 |
|----------|----------|----------|



| CATEGORY | A | B | C | D |
|-------------------|-----------------------|-----------------------|-------------------------|----|
| LPV DA | 958-1 250 (300-1) | | | NA |
| LNAV/VNAV DA | 958-1 250 (300-1) | | | NA |
| LNAV MDA | 1100-1 | 392 (400-1) | 1100-1½ 392 (400-1½) | NA |
| C CIRCLING | 1140-1 432 (500-1) | 1240-1 532 (600-1) | 1240-1½ 532 (600-1½) | NA |

- REIL Rwy 14 and 21 **ⓘ**
- MIRL Rwy 14-32 **ⓘ**
- HIRL Rwy 3-21 **ⓘ**

NC-3, 20 FEB 2025 to 20 MAR 2025

NC-3, 20 FEB 2025 to 20 MAR 2025