


WAAS CH 50231 W05A	APP CRS 047°	Rwy Idg TDZE 429 Apt Elev 441	5000
--	------------------------	---	-------------


RNAV (GPS) RWY 5

NORTH CENTRAL STATE (SFZ)

RNP APCH - GPS.		MALS	MISSED APPROACH: Climb to 2000 then climbing left turn to 2500 direct FOSTY and hold.
<p>⚠ Circling Rwy 15, 33 NA at night. For inoperative MALS, increase LPV all Cats visibility to 3/8 mile. For inop ALS, increase LPV all Cats visibility to 3/8 SM and LNAV/VNAV all Cats visibility to 1 1/8 SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.</p>			
AWOS-3PT 120.775	PROVIDENCE APP CON * 123.675 244.875	CLNC DEL 124.35	UNICOM 123.075 (CTAF) 0



WALLU		2000	2500	FOSTY
2600	047°	MIMIC 2500	IDIKE 3 NM to RW05	1.1 NM to RW05
GP 3.00°	2500	*1420	RW05	
TCH 52	5.9 NM	3.4 NM	1.9 NM	1.1
CATEGORY	A	B	C	D
LPV DA	700-3/4	271 (300-3/4)		NA
LNAV/VNAV DA	835-1	406 (400-1)		NA
LNAV MDA	820-3/4	391 (400-3/4)	820-7/8 391 (400-7/8)	NA
CIRCLING	900-1	459 (500-1)	900-1 1/2 459 (500-1 1/2)	NA



NE-1, 20 FEB 2025 to 20 MAR 2025

NE-1, 20 FEB 2025 to 20 MAR 2025