

WAAS CH <b>86735</b> <b>W36A</b>	APP CRS <b>001°</b>	Rwy Idg TDZE <b>401</b> Apt Elev <b>402</b>
--	------------------------	---



# RNAV (GPS) RWY 36

OLIVE BRANCH/TAYLOR FLD (OLV)

**▼** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Memphis Intl altimeter setting and increase all DA 32 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C and D and Circling Cats C and D visibility ¼ mile. VDP and Baro-VNAV NA with Memphis Intl altimeter setting. Rwy 36 helicopter visibility reduction below ¾ SM NA.


**▲** MISSED APPROACH: Climb to 1500 then climbing right turn to 2000 direct DOCAP and hold.

ATIS <b>119.925</b>	MEMPHIS APP CON <b>125.8 338.3</b>	OLIVE BRANCH TOWER ★ <b>125.275 (CTAF) 0</b>	GND CON <b>121.2</b>	CLNC DEL <b>121.2</b>	CLNC DEL <b>121.3</b> (When twr closed)	UNICOM <b>122.95</b>
------------------------	---------------------------------------	---	-------------------------	--------------------------	---	-------------------------



1061  
▲

ELEV <b>402</b>	TDZE <b>401</b>
-----------------	-----------------



1500	2000	DOCAP	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 31).	
▲	↷	✦		
*LNAV only	*1.8 NM to RW36	CICAL 2000	DOCAP 4 NM Holding Pattern	
		← 001°	← 001° → 2000	
		↘ 2000	GP 3.00° TCH 45	
	1.8 NM	3.1 NM	7 NM	
CATEGORY	A	B	C	D
LPV DA		709-1	308 (400-1)	
LNAV/VNAV DA		915-1¾	514 (600-1¾)	
LNAV MDA	1000-1	599 (600-1)	1000-1¾	599 (600-1¾)
<b>C</b> CIRCLING	1060-1	658 (700-1)	1060-1¾	1200-2½ 798 (800-2½)

SC-4, 20 FEB 2025 to 20 MAR 2025

SC-4, 20 FEB 2025 to 20 MAR 2025