

LOC/DME I-EKY 111.75 Chan 54 (Y)	APP CRS 053°	Rwy Idg 6007	TDZE 700	Apt Elev 700
---	------------------------	-----------------	-------------	-----------------



ILS or LOC RWY 5

BESSEMER (EKY)


NA When local altimeter setting not received, use Alabaster altimeter setting and increase DA 41 feet, increase all MDAs 60 feet; increase S-LOC 5 Cat C visibility 1/8 SM and Cat D visibility 1/4 SM, increase Circling Cat C visibility 1/8 SM Cat D visibility 1/4 SM, increase JURAM fix S-LOC 5 Cat C visibility 1/8 SM and Cat D visibility 1/4 SM; increase Circling Cat D visibility 1/4 SM. VDP NA with Alabaster altimeter setting.

MISSED APPROACH: Climb to 1200 then climbing left turn to 3000 direct OKW VORTAC and hold.

AWOS-3PT 118.825	BIRMINGHAM APP CON 124.9 351.85	CLNC DEL 123.75	UNICOM 123.0 (CTAF)
----------------------------	---	---------------------------	-------------------------------



CATEGORY	A	B	C	D
S-ILS 5	900-3/4		200 (200-3/4)	
S-LOC 5	1200-1	500 (500-1)	1200-1 3/8 500 (500-1 3/8)	1200-1 1/2 500 (500-1 1/2)
CIRCLING	1200-1	500 (500-1)	1220-1 1/2 520 (600-1 1/2)	1320-2 620 (700-2)
JURAM FIX MINIMUMS				
S-LOC 5	1100-1	400 (400-1)	1100-1 1/8 400 (400-1 1/8)	1100-1 1/4 400 (400-1 1/4)
CIRCLING	1200-1	500 (500-1)	1220-1 1/2 520 (600-1 1/2)	1320-2 620 (700-2)



SE-4, 20 FEB 2025 to 20 MAR 2025

SE-4, 20 FEB 2025 to 20 MAR 2025