ILS or LOC RWY 13R

WILLIAM P HOBBY (HOU)

LOC/DME I-PRQ	APP CRS	Rwy Idg	6568
111.3	131°	TDZE	46
Chan 50		Apt Elev	46

RADAR or DME required for LOC only.
RADAR required for procedure entry.

▼ Inop table does not apply to S-ILS Rwy 13R. Rwy 13R helicopter visibility reduction below ¾ SM NA. For inop ALS, increase S-LOC 13R Cats A/B visibility to RVR 5500, Cats C/D/E to 1⅜ SM.

▲

MALSR

MISSED APPROACH: Climb to 800 then climbing right turn to 2200 direct VUH VOR/DME.

D-ATIS	HOUSTON APP CON	HOBBY TOWER	GND CON	CLNC DEL	CPDLC
124.6	120.05 379.1 EAST 124.35 316.15 WEST	118.7 256.9	121.9	125.45	





REIL Rwy 31L
MIRL Rwy 13L-31R
HIRL Rwys 4-22 and 13R-31L
TDZ/CL Rwys 4, 13R and 31L

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58



CATEGORY	A	B	C	D	E
S-ILS 13R	296/40 250 (300-¾)				
S-LOC 13R	540/40 494 (500-¾)		540/50 494 (500-1)		540/60 494 (500-1¼)
C CIRCLING	540-1 494 (500-1)		740-2¼ 694 (700-2¼)		860-3 814 (900-3)

SC-5, 20 MAR 2025 to 17 APR 2025
SC-5, 20 MAR 2025 to 17 APR 2025