ILS or LOC RWY 36C

MEMPHIS INTL (MEM)

LOC/DME I-TSE	APP CRS	Rwy Idg	10715
110.5	360°	TDZE	341
Chan 42		Apt Elev	341

For inoperative ALS, increase S-ILS 36C Cat E visibility to RVR 4000 and S-LOC 36C Cat C/D/E visibility to RVR 6000. DME or RADAR required. Simultaneous approach authorized with Rwy 36L.

ALSF-2

MISSED APPROACH: Climb to 3000 via MEM VORTAC R-360 to LAURI INT/MEM 13.7 DME and hold.

MEMPHIS APP CON			MEMPHIS TOWER			GND CON		
119.1	291.6	(176°-355°)	(Rwy 9-27)	118.3	257.8	(Rwy 9-27)	121.0	379.2
125.8	338.3	(356°-175°)	(Rwys 18C-36C, 18L-36R)	119.7	257.8	(Rwys 18C-36C, 18L-36R)	121.9	379.2
			(Rwy 18R-36L)	128.425	257.8	(Rwy 18R-36L)	121.65	379.2

D-ATIS 127.75

CLNC DEL 125.2

CPDLC

RADAR REQUIRED

ALTERNATE MISSED APCH FIX

GOBLE HLI 37.2 RADAR

137° 317° R-317 112.4 HLI Chan 71

MEMPHIS 117.5 MEM Chan 122

LOCALIZER 110.5 I-TSE Chan 42

MEM R-360

1337 1450 720 1001 602 506 753 483 881

GINIE I-TSE 6.9 RADAR

MISSED APCH FIX

113.0 GQE R-100 Chan 77

LAURI INT MEM 13.7

80° 360° R-360

117.5 MEM Chan 122

MSA MEM 25 NM

135° 2500 2100 315°

360° (6.3) 2000

(IF) NESBT INT I-TSE 13.2 RADAR

R-277 112.4 HLI Chan 71

180°

ELEV 341 D TDZ 341

TWR 621

18L 18R 36L 36R 9 27

8946 X 150 0.3% UP 0.6% DOWN

11120 X 150 0.7% UP 0.8% DOWN

9220 X 150 0.5% DOWN 0.6% DOWN

9000 X 150 0.5% DOWN

TDZ/CL Rwys 18L, 18C, 18R, 36R, 36C, and 36L HIRL all Rwys

360°

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

3000 MEM R-360 LAURI INT

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 71).

GINIE I-TSE 6.9 RADAR

NESBT INT I-TSE 13.2 RADAR

I-TSE 1.9 I-TSE 3 2000 360° 3000 2000

GS 3.00° TCH 60

1.1 NM 3.9 NM 6.3 NM

CATEGORY	A	B	C	D	E
S-ILS 36C	541/18 200 (200-½)				541/24 200 (200-½)
S-LOC 36C	760/24 419 (500-½)		760/40 419 (500-¾)		760/50 419(500-1)
C CIRCLING	940-1 599 (600-1)		940-1½ 599 (600-1½)	1020-2¼ 679 (700-2¼)	1140-2¾ 799 (800-2¾)

SE-1, 20 MAR 2025 to 17 APR 2025