

# OLGUY THREE DEPARTURE (RNAV)


SC-1, 20 MAR 2025 to 17 APR 2025

ATIS 128.725  
GND CON 121.7  
WILEY POST TOWER \* 126.9 306.9  
OKE CITY DEP CON 124.6 266.8

### TAKEOFF MINIMUMS:

Rwys 13, 17L/R, 31, 35L/R:

Standard with minimum climb of 500' per NM to 2100.



### DEPARTURE ROUTE DESCRIPTION

**TAKEOFF RWY 13:** Climb heading 131° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to BEEDI, thence . . . .

**TAKEOFF RWYS 17L/R:** Climb on heading 176° to 1800, then right turn heading 201° or as assigned by ATC, expect RADAR vectors to BEEDI, thence . . . .


**TAKEOFF RWY 31:** Climb on heading 311° to 1800, then right turn heading 336° or as assigned by ATC, expect RADAR vectors to BEEDI, thence . . . .

**TAKEOFF RWYS 35L/R:** Climb on heading 356° to 1800, then left turn heading 336° or as assigned by ATC, expect RADAR vectors to BEEDI, thence . . . .

. . . . on track 267° to OLGUY then on (transition). Maintain 3000 or as assigned by ATC. Expect filed altitude 10 minutes after departure.

**GRUVN TRANSITION (OLGUY3.GRUVN):**  
**YOUSE TRANSITION (OLGUY3.YOUSE):**

### TOP ALTITUDE: Assigned by ATC



NOTE: RADAR required.  
NOTE: DME/DME/IRU or GPS required.  
NOTE: RNAV 1.

NOTE: Chart not to scale.

SC-1, 20 MAR 2025 to 17 APR 2025