



POTTR TWO DEPARTURE


ANCHORAGE DEP CON
126.4 270.25
D-ATIS
135.5
CLNC DEL
119.4 323.1
GND CON
121.9 338.25
ANCHORAGE TOWER
118.3 257.8


RADAR required.


**TOP ALTITUDE:
4000**


SPARREVOHN
117.2 SQA 
Chan 119


KENAI
117.6 ENA 
Chan 123



JOHNSTONE POINT
116.7 JOH 
Chan 114

HOMER
114.6 HOM 
Chan 93

MIDDLETON ISLAND
115.3 MDO 
Chan 100



TAKEOFF MINIMUMS

Rwys 15, 25L/R, 33: NA - ATC.

Rwy 7L: 300-1½ or standard with minimum climb of 255 feet per NM to 400.

Rwy 7R: 300-1 or standard with minimum climb of 285 feet per NM to 400.

NOTE: Do not exceed 200K.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 7L/R: Climb on heading 074° to 600, then climbing right turn on heading 199°. Thence. . . .

. . . . expect RADAR vectors to assigned route or depicted fix. Maintain 4000. Expect further clearance to filed altitude within 10 minutes after departure.

POTTR TWO DEPARTURE

AK, 20 FEB 2025 to 17 APR 2025

AK, 20 FEB 2025 to 17 APR 2025